

LOCATION 503 Cobb St CITY Gaston, NC
BETWEEN Clark Ave. STREET & Flint St. STREET

	SIZE	TYPE	LENGTH	INSTALLED	RETIRED	RENEWED
MAIN TO BLDG	<u>3/4"</u>	<u>S</u>	<u>replaced</u>	<u>3/4"</u>		<u>10-4-02</u>
MAIN TO PROP LINE	<u>3/4"</u>	<u>S</u>	<u>C.W. Riser</u>			<u>"</u>
PROP. LINE TO BLDG	<u>3/4"</u>	<u>S</u>				<u>"</u>

ENTERS 503 BRANCHED INTO 0

TAP SIZE: _____ PRESSURE _____ PSI _____ INCHES W C LOCATION 480' south of
corner of Flint St.


PRESSURE TEST @ _____ PSI FOR _____ HRS BY _____

MAIN-SIZE _____ C I _____ BARE STEEL _____ COATED STEEL _____ PLASTIC _____ YEAR INSTALLED _____

DEPTH: _____ FT _____ IN LOCATION 69' west of center of Cobb St.

"A" P/S READING 1.04 TOTAL ANODES 1# 0 17# 0 L.R. # 0

REMARKS replaced riser



Test Station		
Reading & Location	Lead	Volts
P/S Pipeline Lead - Red New Service	<u>S</u>	
P/S Pipeline Lead - White Existing Main	<u>E</u>	