

LOCATION 1912 Flint Ln. CITY Castroville  
BETWEEN \_\_\_\_\_ STREET & \_\_\_\_\_ STREET

	SIZE	TYPE	LENGTH	INSTALLED	RETIRED	RENEWED
MAIN TO BLDG	<u>3/4"</u>	<u>P</u>	<u>20'</u>	<u>11-12-01</u>		
MAIN TO PROP LINE	<u>3/4"</u>	<u>P</u>	<u>0</u>			
PROP LINE TO BLDG	<u>3/4"</u>	<u>P</u>	<u>20'</u>			


ENTERS 1912 BRANCHED INTO \_\_\_\_\_  
TAP SIZE 3/4" PRESSURE 60 PSI \_\_\_\_\_ INCHES W.C. LOCATION 285' E. of center of  
Lane NO. 3

PRESSURE TEST @ 60 PSI FOR 44 HRS BY S.M.  
MAIN-SIZE 3/4" C I \_\_\_\_\_ BARE STEEL \_\_\_\_\_ COATED STEEL \_\_\_\_\_ PLASTIC / YEAR INSTALLED \_\_\_\_\_

DEPTH 2 FT 0 IN LOCATION 60' N. of center of Flint Ln

"A" P/S READING P TOTAL ANODES 1# 2 17# 2 LR # \_\_\_\_\_

REMARKS \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_



Test Station		
Reading & Location	Lead	Volts
P/S Pipeline Lead - Red New Service	<u>S</u>	
P/S Pipeline Lead - White Existing Main	<u>E</u>	